



**SAFETY DATA SHEET**  
**DASH & TRIM SHEEN (VARIOUS FRAGRANCES)**

**SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING**

**1.1. Product identifier**

Product name DASH & TRIM SHEEN (VARIOUS FRAGRANCES)  
Product No. DH018-DH021

**1.2. Relevant identified uses of the substance or mixture and uses advised against**

Identified uses As product description

**1.3. Details of the supplier of the safety data sheet**

Supplier Manufactured for PMA  
83 Ducie Street  
Manchester  
M1 2JQ  
+44 (0)333 313 3349  
info@pmachemicals.co.uk

**1.4. Emergency telephone number**

**SECTION 2: HAZARDS IDENTIFICATION**

**2.1. Classification of the substance or mixture**

Classification (EC 1272/2008)  
Physical and Chemical Hazards Flam. Aerosol 1 - H222  
Human health Skin Irrit. 2 - H315;STOT SE 3 - H336  
Environment Aquatic Chronic 2 - H411  
Classification (1999/45/EEC) Xi;R38. F+;R12. N;R51/53. R67.  
The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

**2.2. Label elements**

Label In Accordance With (EC) No. 1272/2008



Signal Word Danger

Hazard Statements  
H222 Extremely flammable aerosol.  
H315 Causes skin irritation.  
H336 May cause drowsiness or dizziness.  
H411 Toxic to aquatic life with long lasting effects.

Precautionary Statements  
P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.  
P271 Use only outdoors or in a well-ventilated area.  
P280 Wear protective gloves/protective clothing/eye protection/face protection.  
P501 Dispose of contents/container to ...

Supplementary Precautionary Statements  
P211 Do not spray on an open flame or other ignition source.  
P251 Pressurized container: Do not pierce or burn, even after use.

## DASH & TRIM SHEEN (VARIOUS FRAGRANCES)

|          |  |
|----------|--|
| P273     | Avoid release to the environment.  |
| P261     | Avoid breathing vapour/spray.  |
| P264     | Wash contaminated skin thoroughly after handling.  |
| P321     | Specific treatment (see medical advice on this label).   |
| P302+352 | IF ON SKIN: Wash with plenty of soap and water.  |
| P304+340 | IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. |
| P312     | Call a POISON CENTER or doctor/physician if you feel unwell.                                     |
| P332+313 | If skin irritation occurs: Get medical advice/attention.   |
| P362     | Take off contaminated clothing and wash before reuse.  |
| P391     | Collect spillage.  |
| P403+233 | Store in a well-ventilated place. Keep container tightly closed.                                 |
| P405     | Store locked up.   |
| P410+412 | Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122°F.                      |

### 2.3. Other hazards

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

### 3.2. Mixtures

|  |  |
|--|--|
| BUTANE   | 10-30%   |
| CAS-No.: 106-97-8  | EC No.: 203-448-7  |
| Classification (EC 1272/2008)<br>Flam. Gas 1 - H220  | Classification (67/548/EEC)<br>F+;R12  |
| ISOBUTANE  | 5-10%  |
| CAS-No.: 75-28-5   | EC No.: 200-857-2  |
| Classification (EC 1272/2008)<br>Flam. Gas 1 - H220  | Classification (67/548/EEC)<br>F+;R12  |
| NAPHTHA (PETROLEUM) , HYDROTREATED LIGHT   | 30-60%   |
| CAS-No.: 64742-49-0  | EC No.: 921-024-6  |
|  | Registration Number: 01-2119475514-35-xxxx                                       |
| Classification (EC 1272/2008)<br>Flam. Liq. 2 - H225<br>Skin Irrit. 2 - H315<br>STOT SE 3 - H336<br>Asp. Tox. 1 - H304<br>Aquatic Chronic 2 - H411 | Classification (67/548/EEC)<br>Xn;R65.<br>Xi;R38.<br>F;R11.<br>N;R51/53.<br>R67. |
| PROPANE  | 10-30%   |
| CAS-No.: 74-98-6   | EC No.: 200-827-9  |
| Classification (EC 1272/2008)<br>Flam. Gas 1 - H220  | Classification (67/548/EEC)<br>F+;R12  |

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

## SECTION 4: FIRST AID MEASURES

# DASH & TRIM SHEEN (VARIOUS FRAGRANCES)

## **4.1. Description of first aid measures**

### General information

Move the exposed person to fresh air at once. Get medical attention if any discomfort continues.

### Inhalation

Move the exposed person to fresh air at once. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen. Keep the affected person warm and at rest. Get prompt medical attention.

### Ingestion

DO NOT INDUCE VOMITING! Rinse mouth thoroughly with water and give large amounts of milk or water to people not unconscious. Get medical attention if any discomfort continues.

### Skin contact

Wash the skin immediately with soap and water. Get medical attention if any discomfort continues.

### Eye contact

Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.

## **4.2. Most important symptoms and effects, both acute and delayed**

## **4.3. Indication of any immediate medical attention and special treatment needed**

## **SECTION 5: FIREFIGHTING MEASURES**

### **5.1. Extinguishing media**

#### Extinguishing media

Use: Powder. Dry chemicals, sand, dolomite etc. Water spray, fog or mist.

### **5.2. Special hazards arising from the substance or mixture**

#### Unusual Fire & Explosion Hazards

Aerosol cans may explode in a fire.

### **5.3. Advice for firefighters**

#### Special Fire Fighting Procedures

Containers close to fire should be removed or cooled with water. Use water to keep fire exposed containers cool and disperse vapours.

## **SECTION 6: ACCIDENTAL RELEASE MEASURES**

### **6.1. Personal precautions, protective equipment and emergency procedures**

### **6.2. Environmental precautions**

### **6.3. Methods and material for containment and cleaning up**

Wear necessary protective equipment. Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate. Let evaporate. Keep out of confined spaces because of explosion risk. If leakage cannot be stopped, evacuate area.

### **6.4. Reference to other sections**

## **SECTION 7: HANDLING AND STORAGE**

### **7.1. Precautions for safe handling**

Keep away from heat, sparks and open flame. Avoid spilling, skin and eye contact. Ventilate well, avoid breathing vapours. Use approved respirator if air contamination is above accepted level.

### **7.2. Conditions for safe storage, including any incompatibilities**

Aerosol cans: Must not be exposed to direct sunlight or temperatures above 50°C.

### **7.3. Specific end use(s)**

## **SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**

### **8.1. Control parameters**

## DASH & TRIM SHEEN (VARIOUS FRAGRANCES)

| Name                                     | STD | TWA - 8 Hrs  |               | STEL - 15 Min |               | Notes |
|--|-----|--------------|---------------|---------------|---------------|-------|
|  |     |              |               |               |               |       |
| BUTANE                                   | WEL | 600 ppm      | 1450 mg/m3    | 750 ppm       | 1810 mg/m3    |       |
| NAPHTHA (PETROLEUM) , HYDROTREATED LIGHT |     |              | 1200 mg/m3    | 60 ppm        | 216 mg/m3     |       |
| PROPANE                                  |     | Asphyxiating | Asphyxiating. | Asphyxiating  | Asphyxiating. |       |

WEL = Workplace Exposure Limit.

### 8.2. Exposure controls

Protective equipment



Engineering measures

Provide adequate general and local exhaust ventilation.

Respiratory equipment

No specific recommendation made, but respiratory protection must be used if the general level exceeds the recommended occupational exposure limit. Use chemical cartridge protection with appropriate cartridge.

Hand protection

Use protective gloves.

Eye protection

Use approved safety goggles or face shield.

Other Protection

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact.

Hygiene measures

DO NOT SMOKE IN WORK AREA! Wash hands at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. When using do not eat, drink or smoke.

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

### 9.1. Information on basic physical and chemical properties

|                               |                 |
|-------------------------------|-----------------|
| Appearance                    | Aerosol.        |
| Colour                        | Typical         |
| Odour                         | Characteristic. |
| Flammability Limit - Lower(%) | 0.8             |
| Flammability Limit - Upper(%) | 9.0             |

### 9.2. Other information

## SECTION 10: STABILITY AND REACTIVITY

### 10.1. Reactivity

### 10.2. Chemical stability

Stable under normal temperature conditions.

### 10.3. Possibility of hazardous reactions

### 10.4. Conditions to avoid

Avoid heat, flames and other sources of ignition. Avoid contact with: Strong oxidising agents. Strong alkalis. Strong mineral acids.

### 10.5. Incompatible materials

### 10.6. Hazardous decomposition products

Fire creates: Vapours/gases/fumes of: Carbon monoxide (CO). Carbon dioxide (CO<sub>2</sub>).

# DASH & TRIM SHEEN (VARIOUS FRAGRANCES)

## SECTION 11: TOXICOLOGICAL INFORMATION

### 11.1. Information on toxicological effects

#### Inhalation

May cause irritation to the respiratory system. Vapours may cause headache, fatigue, dizziness and nausea. Prolonged inhalation of high concentrations may damage respiratory system. Irritating to respiratory system.

#### Ingestion

May cause discomfort if swallowed. May cause stomach pain or vomiting. Gastrointestinal symptoms, including upset stomach.

#### Skin contact

Prolonged or repeated exposure may cause severe irritation. Acts as a defatting agent on skin. May cause cracking of skin, and eczema. May cause allergic contact eczema. May cause sensitisation by skin contact. Irritating to skin.

#### Eye contact

Irritating to eyes. May cause chemical eye burns.

#### Route of entry

Inhalation. Skin and/or eye contact.

## SECTION 12: ECOLOGICAL INFORMATION

#### Ecotoxicity

Dangerous for the environment if discharged into watercourses.

### 12.1. Toxicity

### 12.2. Persistence and degradability

### 12.3. Bioaccumulative potential

### 12.4. Mobility in soil

### 12.5. Results of PBT and vPvB assessment

### 12.6. Other adverse effects

## SECTION 13: DISPOSAL CONSIDERATIONS

### 13.1. Waste treatment methods

Empty containers must not be burned because of explosion hazard. Dispose of waste and residues in accordance with local authority requirements.

## SECTION 14: TRANSPORT INFORMATION

### 14.1. UN number

|                      |      |
|----------------------|------|
| UN No. (ADR/RID/ADN) | 1950 |
| UN No. (IMDG)        | 1950 |
| UN No. (ICAO)        | 1950 |

### 14.2. UN proper shipping name

|                      |          |
|----------------------|----------|
| Proper Shipping Name | AEROSOLS |
|----------------------|----------|

### 14.3. Transport hazard class(es)

|                   |                |
|-------------------|----------------|
| ADR/RID/ADN Class | 2              |
| ADR/RID/ADN Class | Class 2: Gases |
| ADR Label No.     | 2.1            |
| IMDG Class        | 2.1            |

# DASH & TRIM SHEEN (VARIOUS FRAGRANCES)

ICAO Class/Division

2.1

Transport Labels



## **14.4. Packing group**

ADR/RID/ADN Packing group Not Applicable

IMDG Packing group Not Applicable

ICAO Packing group Not Applicable

## **14.5. Environmental hazards**

Environmentally Hazardous Substance/Marine Pollutant

No.

## **14.6. Special precautions for user**

EMS F-D, S-U

## **14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code**

### SECTION 15: REGULATORY INFORMATION

#### **15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

Uk Regulatory References

The Chemicals (Hazard Information and Packaging for Supply) Regulations 2002.

The Control of Substances Hazardous to Health Regulations 2002.

Statutory Instruments

The Control of Substances Hazardous to Health Regulations 2002.

The Chemicals (Hazard Information and Packaging for Supply) Regulations 2002.

Approved Code Of Practice

Classification and Labelling of Substances and Preparations Dangerous for Supply.

Guidance Notes

Workplace Exposure Limits EH40.

Introduction to Local Exhaust Ventilation HS(G)37.

CHIP for everyone HSG(108).

#### **15.2. Chemical Safety Assessment**

### SECTION 16: OTHER INFORMATION

Revision Date 06/10/2015

Revision 1

Supersedes date 12/04/2013

Risk Phrases In Full

R12 Extremely flammable.

R65 Harmful: may cause lung damage if swallowed.

R11 Highly flammable

R38 Irritating to skin.

R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R67 Vapours may cause drowsiness and dizziness.

## DASH & TRIM SHEEN (VARIOUS FRAGRANCES)

### Hazard Statements In Full

|      |  |
|------|--|
| H315 | Causes skin irritation.                          |
| H222 | Extremely flammable aerosol.                     |
| H220 | Extremely flammable gas.                         |
| H225 | Highly flammable liquid and vapour.              |
| H304 | May be fatal if swallowed and enters airways.    |
| H336 | May cause drowsiness or dizziness.               |
| H411 | Toxic to aquatic life with long lasting effects. |